

BALETITE®

Less silage losses*



Easy opening*



Simplified recycling*



For Silage.

Baletite has been created for baling machines that can apply film instead of net. Baletite provides extra layers of protection and creates an extra oxygen barrier where it matters most, resulting in less white mould growth and fewer silage losses.

Width (mm)	Thickness (µm)	Length (m)	Reel Weight (kg)	Reels Per Pallet (#)
Edge-to-edge Coverage				
1280	16	2000	40	20
Over-edge Coverage				
1380	16	2000	43	20
1330**	15	3000	58	16

**Product range varies according to region



Up to 258 bales per reel
More baling, less stopping†

For Haylage and Stemmy Crops.

This Baletite is specifically designed for stemmy crops, higher dry matter contents and more challenging conditions. The film enables hassle free application, with a high strength and tear resistance for optimal feed preservation.

Width (mm)	Thickness (µm)	Length (m)	Reel Weight (kg)	Reels Per Pallet (#)
Edge-to-edge Coverage				
1280**	20	1650	41	20
Over-edge Coverage				
1380	20	1650	45	20

**UV Protected – Recommended option for single balers




For Compactors

This Baletite range is specifically developed for compactor machinery. As the film is stronger, the use of less layers of film is possible with a higher break tension setting on the machinery.

Width (mm)	Thickness (µm)	Length (m)	Reel Weight kg	Reels
1280	13	2400	39	20
1280	16	2000	40	20
1280**	13	3500	56	16
950**	13	2400	29	20
680**	16	2000	21	20

**Product range varies according to region



*Compared to netwrap. †Compared to Baletite 2000m, 16µm.